

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number
WO 2004/039167 A1

- (51) International Patent Classification⁷: A23G 3/00, 1/00 (74) Agent: WARD, David, I.; Marks & Clerk, Alpha Tower
Queensway, Birmingham B1 1TT (GB).
- (21) International Application Number:
PCT/GB2003/004624 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 28 October 2003 (28.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0225087.6 29 October 2002 (29.10.2002) GB (84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (*for all designated States except US*): CAD-
BURY SCHWEPPEs PLC [GB/GB]; 25 Berkeley
Square, London W1J 6HB (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): SANDERS, Nigel,
Hugh [GB/CA]; 317 Runnymede Road, Toronto, Ontario
M6S 2Y5 (CA). SMITH, Ian, Humphrey [GB/GB];
Woodlands, Flowers Hill, Pangbourne, Reading Berkshire
RG8 7BD (GB). BROWN, Anthony, James [GB/GB]; 83
Admirals Court, Rose Kiln Lane, Reading, Berkshire RG1
6SS (GB). MINVILLE, Benoit [CA/CA]; 207 Maher
Street, Shefford, Quebec J2G 9J (CA).
- Published:
— with international search report
— before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments
- For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: METHOD OF PREPARING MOULDED CONFECTIONERY ARTICLES

(57) Abstract: The present invention discloses a method of preparing moulded confectionery articles, comprising the steps of: (1) preparing a liquid candy composition which solidifies upon cooling, said liquid candy composition being at a first temperature; (2) preparing a liquid chocolate composition which solidifies upon cooling, said liquid chocolate composition being at a second temperature which is lower than said first temperature; (3) co-depositing the liquid candy composition and the liquid chocolate compositions in the moulds; and (4) cooling the moulded compositions in the moulds so as to solidify the moulded compositions to form moulded confectionery articles; wherein the liquid chocolate composition is subjected to a high shear of at least 100s⁻¹, before being co-deposited in the moulds. This treatment enables the candy composition to be deposited into the moulds at a temperature which is higher than has heretofore been considered possible.

WO 2004/039167 A1

THIS PAGE BLANK (USP 10)

METHOD OF PREPARING MOULDED CONFECTIONERY ARTICLES

This invention relates to a method of preparing moulded confectionery articles and is more concerned with a method of preparing moulded confectionery articles comprising both a candy composition and a chocolate composition.

It is known to prepare moulded confectionery articles comprising a candy outer layer with an inner core formed of chocolate. However, problems arise when moulding such confectionery articles because the candy composition needs to be deposited in the moulds at a relatively high temperature to enable the candy to flow properly. On the other hand, chocolate suffers from the disadvantage that, when it is heated above a critical temperature, it exhibits a sharp increase in viscosity making it virtually impossible to mould successfully. This critical temperature is generally in the range of about 50°C to 120°C but depends upon the nature of the chocolate formulation. The critical temperature is higher for dark chocolate (i.e. chocolate containing no milk solids) than for milk and white chocolate, both of which contain milk solids. This sharp increase in viscosity also occurs with chocolate compound coatings.

Furthermore, chocolate also tends to degrade when exposed for extended periods of time to temperatures rather lower than the critical temperatures. Thus, it is common to set practical upper temperature limits when handling chocolate. The limits are typically set at 85°C for dark chocolate, and 75°C for milk and white chocolates. Above these temperatures, the viscosity of the chocolate increases, and extended holding times causes flavour degradation, and eventually the product solidifies into an unworkable mass.

It is an object of the present invention to provide an improved method of preparing moulded confectionery articles which enables the above-mentioned problems to be mitigated.

According to the present invention, there is provided a method of preparing moulded confectionery articles, comprising the steps of:

- (1) preparing a liquid candy composition which solidifies upon cooling, said liquid candy composition being at a first temperature;
- (2) preparing a liquid chocolate composition which solidifies upon cooling, said liquid chocolate composition being at a second temperature which is lower than said first temperature;
- (3) co-depositing the liquid candy composition and the liquid chocolate composition in moulds; and
- (4) cooling the moulded compositions in the moulds so as to solidify the moulded compositions to form moulded confectionery articles;

wherein the liquid chocolate composition is subjected to a high shear of at least 100 s^{-1} , preferably up to 5000 s^{-1} , before being co-deposited in the moulds.

By subjecting the liquid chocolate composition to a high shear before it is co-deposited into the moulds, it is found that the liquid chocolate composition can remain mouldable at temperatures above the temperature at which it normally exhibits a sharp increase in viscosity. Thus, this procedure enables the candy composition to be deposited into the moulds at a temperature which is higher than has heretofore been considered possible.

Co-depositing the candy composition and the chocolate composition in the mould ensures that the chocolate composition is exposed to the higher first

temperature for only a relatively short period of time, thus reducing the risk of flavour degradation and product solidification.

For example, it is found that, even when the chocolate composition is a milk chocolate composition, it can be successfully co-deposited with a liquid candy composition at temperatures as high as 150°C using a one-shot co-depositor, if the chocolate composition is subjected to a high shear of at least 100 s⁻¹, and preferably at about 500 s⁻¹, and preferably up to 5000 s⁻¹.

The candy composition may be any sugar-based candy composition such as a hard candy composition or a caramel composition. These are generally compositions which are produced by boiling a sugar syrup to a temperature of about 150°C and introducing flavourings into the cooked sugar. These high boiling compositions must be deposited at at least about 135°C to avoid so-called "tailing" during depositing. In contrast, the chocolate composition is maintained at a much lower temperature (typically about 40°C) up until the time when it is co-deposited with the candy composition. At which time, it becomes heated to about 135°C as a result of heat transfer from the candy composition.

In the case where the chocolate composition to be deposited has a relatively low critical temperature, in addition to subjecting it to a high shear, it is also within the scope of the invention to include a minor amount of dark chocolate (e.g. up to about 10%) so as to increase its critical temperature. However, this procedure does suffer from the disadvantage that the taste of the chocolate is changed and may also increase the cost of production.

It is further possible to improve the viscosity characteristics of the chocolate being moulded by increasing the fat content by, for example, addition of cocoa butter in an amount of at least 1% by weight and preferably at least 2% by weight.

Preferably, the chocolate is subjected to a high shear in the range of 100 to 1000 s^{-1} , more preferably 200 to 500 s^{-1} before being deposited into the moulds.

The chocolate composition may be subjected to high shear either in the depositor itself immediately prior to being introduced into the moulds, or it may be subjected to high shear prior to being passed to the depositor.

However, it is important to effect such shearing at a stage when the chocolate will not lose its advantageous viscosity characteristics before being deposited into the moulds.

In one series of embodiments, the chocolate composition is subjected to high shear prior to being passed into the depositor and in the depositor itself, the first shearing process being referred to hereinafter as "pre-shear". Preferably, said pre-shear is from about 100 s^{-1} to 5000 s^{-1} . More preferably, the chocolate composition is subjected to a pre-shear which is greater than the subsequent shear in the depositor.

An example of the present invention will now be described in more detail.

Recipe

	Ingredient	% by weight
1)	Premix of Liquid sugar Glucose Syrup	54.3 35.5
2)	Flavour	0.2
3)	Milk Chocolate coating (see Example below)	10.0

Process

1. The pre-mix was batch weighed into a heated tank.
2. The pre-mix was transferred via a small buffer tank to a pre-cooker and heated to 126 °C.
3. The pre-mix was then transferred to a Microfilm vacuum cooker where it was cooked at 150°C in a vacuum of 3 inHg (10.2 kPa).
4. The flavour was mixed into the cooked candy mass which was then transferred to the depositor hopper (temperature 140 °C).
5. Molten chocolate coating at 40 °C was pumped to the depositor hopper (temperature 50°C).
6. The cooked candy mass and the chocolate were co-deposited through a manifold plate at 135 °C into moulds, at a speed of 70 strokes per minute (Baker Perkins (APV) model 156 depositer.156/049).
7. The moulds were immediately transferred into a cooling tunnel set to 25°C and 35% RH (relative humidity) to harden and cool down the candy
8. The candies were then de-moulded and fed automatically via conveyors to wrapping machines.

The average shear rate experienced by the chocolate in the narrowest section of the depositor (i.e. the depositor nozzle) was calculated to be 245s^{-1} (i.e. half the shear rate experienced at the wall of the depositor nozzle, assuming Newtonian flow behaviour).

Example Milk chocolate coating composition	% by weight
Milk chocolate crumb	69.8
Cocoa butter equivalent	21.9
Butter oil	0.3
Soya lecithin	0.3
Sugar	4.2
Cocoa liquor	3.4
Flavour	0.1

In a modification of the above Example, the molten chocolate composition is subjected to a pre-shear in an in-line shear mixer prior to being pumped into the depositor.

CLAIMS

1. A method of preparing moulded confectionery articles, comprising the steps of:
 - (1) preparing a liquid candy composition which solidifies upon cooling, said liquid candy composition being at a first temperature;
 - (2) preparing a liquid chocolate composition which solidifies upon cooling, said liquid chocolate composition being at a second temperature which is lower than said first temperature;
 - (3) co-depositing the liquid candy composition and the liquid chocolate composition in moulds; and
 - (4) cooling the moulded compositions in the moulds so as to solidify the moulded compositions to form moulded confectionery articles;wherein the liquid chocolate composition is subjected to a high shear of at least 100s^{-1} , before being co-deposited in the moulds.
2. The method of claim 1, wherein the liquid chocolate composition is subjected to a shear of from 100 to 1000s^{-1} .
3. The method of claim 1, wherein the liquid chocolate composition is subjected to a shear of from 200 to 500s^{-1} .
4. The method of any preceding claim wherein the candy composition is a hardy candy or caramel composition and the first temperature is from 135°C up to 150°C .

5. The method of any preceding claim wherein the second temperature is about 40°C.
6. The method of any preceding claim wherein the chocolate composition is a milk chocolate composition.
7. The method of claim 6, wherein up to 10% dark chocolate is added to the milk chocolate composition prior to step (3).
8. The method of any preceding claim wherein additional fat is added to the chocolate composition so as to increase its fat content by at least 1% by weight, prior to step (3).
9. The method of any preceding claim wherein the chocolate composition is subjected to the high shear in the depositor immediately prior to being introduced into the moulds during step (3).
10. The method of any one of claims 1 to 8, wherein the chocolate composition is subjected to the high shear prior to step (iii).
11. The method of claim 9 wherein the chocolate composition is subjected to a pre-shear prior to step (iii).
12. The method of claim 11, wherein the pre-shear is in the range of from 100s^{-1} to 5000s^{-1} .
13. The method of claim 11 or 12, wherein the pre-shear is greater than the high shear.

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/GB 03/04624

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 A23G3/00 A23G1/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A23G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, PAJ, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4 229 484 A (STEELS GORDON ET AL) 21 October 1980 (1980-10-21) column 2, line 61 - column 3, line 23; claims; figures 5-12	1-6, 10-13
Y	WO 96 39045 A (KRAFT FOODS INC) 12 December 1996 (1996-12-12) page 5, line 35 - page 6, line 21; examples	1-6, 10-13
A	US 1 711 750 A (CHRISTOPHER SCHOPPNER WILLIAM) 7 May 1929 (1929-05-07) page 1, line 41 - line 49; figures page 2, line 45 - line 65	1-13
Y	US 4 517 205 A (ALDRICH DEBORAH G) 14 May 1985 (1985-05-14) column 3, line 25 - line 40; claims 1,12-18; examples	1-6, 10-13
	--- -/-	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

19 February 2004

Date of mailing of the international search report

01/03/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Guyon, R

INTERNATIONAL SEARCH REPORT

Internat. Application No.
PCT/GB 4624

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE 195 03 635 A (TSCHUSCHNER HORST DIETER PROF) 16 November 1995 (1995-11-16) column 5, line 51 -column 6, line 40 column 3, line 7 - line 37	1-6, 10-13
A	US 6 238 724 B1 (HINE WILLIAM SCOTT ET AL) 29 May 2001 (2001-05-29) the whole document	1-13
A	US 5 264 234 A (WINDHAB ERICH ET AL) 23 November 1993 (1993-11-23) the whole document	1-13
A	GB 1 386 469 A (STORCK AUGUST GMBH) 5 March 1975 (1975-03-05)	

INTERNATIONAL SEARCH REPORT

International Publication No

PCT/GB 03/04624

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4229484	A	21-10-1980	DE 2914543 A1 GB 2018668 A ,B	18-10-1979 24-10-1979
WO 9639045	A	12-12-1996	AT 410747 B AT 900696 A AU 5443096 A CA 2196577 A1 CH 690640 A5 DE 19680669 T0 DK 12797 A ES 2131486 A1 FI 970472 A GB 2305105 A ,B LU 90023 A1 SE 520657 C2 SE 9700453 A WO 9639045 A1 US 5676995 A	25-07-2003 15-12-2002 24-12-1996 12-12-1996 30-11-2000 18-09-1997 25-03-1997 16-07-1999 04-04-1997 02-04-1997 16-04-1997 05-08-2003 19-02-1997 12-12-1996 14-10-1997
US 1711750	A	07-05-1929	NONE	
US 4517205	A	14-05-1985	NONE	
DE 19503635	A	16-11-1995	DE 19503635 A1	16-11-1995
US 6238724	B1	29-05-2001	BR 9915631 A EP 0997076 A2 NO 995287 A PL 336335 A1 SK 150399 A3	21-08-2001 03-05-2000 02-05-2000 08-05-2000 11-07-2000
US 5264234	A	23-11-1993	DE 4125463 A1 DE 59205078 D1 EP 0525524 A1	04-02-1993 29-02-1996 03-02-1993
GB 1386469	A	05-03-1975	DE 2201891 A1 AT 316297 B BE 791874 A1 CH 552947 A FR 2167536 A1 IT 971534 B NL 7215383 A SE 390870 B	26-07-1973 10-07-1974 16-03-1973 30-08-1974 24-08-1973 10-05-1974 17-07-1973 31-01-1977

THIS PAGE BLANK (USPTO)